

TECHNICAL DATA SHEET



DYNOSPLIT® AP

Small Dia. Detonator Sensitive Continuous Packaged Emulsion

Properties

SDS
#1030

Density (g/cc) Avg	1.08
Energy ^a (cal/g)	775
(cal/cc)	840
Relative Weight Strength ^a	0.88
Relative Bulk Strength ^{a,b}	1.16
Velocity ^c (m/s)	4,700
(ft/s)	15,400
Detonation Pressure ^c (kbars)	60
Gas Volume ^a (moles/kg)	41
Water Resistance	Excellent
Fume Class ^d	IME1 & NRCan1

a All Dyno Nobel Inc. energy and gas volume values are calculated using PRODET™, the computer code developed by Dyno Nobel Inc. for its exclusive use. Other computer codes may give different values.

b ANFO = 1.00 @ 0.82 g/cc

c Unconfined @ 32 mm (1¼ in) diameter

d DYNOSPLIT AP is IME Fume Class 1.


Hazardous Shipping Description

- Explosive, Blasting, Type E 1.1D UN 0241 II



PRODUCT DESCRIPTION

DYNOSPLIT AP is a detonator sensitive, continuous, packaged emulsion explosive product that is specifically designed for underground perimeter control applications such as presplitting and trim blasting. DYNOSPLIT AP does not utilize either an internal or attached external detonating cord trace making it an all-purpose, water resistant, cost effective emulsion product for this application. The continuous explosive column provides consistent borehole pressure along the entire loaded borehole zone resulting in a uniform tensile shearing effect. DYNOSPLIT AP is one continuous single cartridge and can be ordered in a standard length so that cutting is not needed, making this product very easy to handle.



APPLICATION RECOMMENDATIONS

- DYNOSPLIT AP is recommended for use with either electric, electronic or nonelectric standard strength detonators or detonating cord.
- When initiating with detonating cord, **ALWAYS** use 5.3 g/m (25 gr/ft) detonating cord when internal product temperatures are higher than 0° C (32° F) or 8.5 g/m (40 gr/ft) detonating cord when internal product temperatures are -20° C to 0° C (-4° to 32° F)
- DYNOSPLIT AP will perform in temperatures from -20° to +50° C (-4° to 122° F). At internal product temperatures higher than -18° C (0° F), **ALWAYS** use a Dyno Nobel standard strength detonator or equivalent. At internal product temperatures below -18° C (0° F) and higher than -23° C (-10° F), **ALWAYS** use a 10 gram or larger cast booster. For internal product temperatures below -23° C (-10° F), consult your Dyno Nobel representative for the recommended cast booster size.
- Emulsion explosives are susceptible to “dynamic shock” and may detonate at low order or fail completely when applied in very wet conditions where explosive charges or decks are closely spaced and/or where geological conditions promote this effect. Consult your Dyno Nobel representative for alternate product recommendations when these conditions exist.

Product Disclaimer: Please see reverse side.

DYNO
Dyno Nobel

TECHNICAL DATA SHEET



DYNOSPLIT® AP

Small Dia. Detonator Sensitive Continuous Packaged Emulsion

Properties Cont.

Packaging

Material Number	Diameter		Weight		Length / Cartridge		Cartridge Count per Case	Net Explosive Weight*		Case
	mm	in	kg/m	lbs/ft	cm	in		kg	lb	
	QG41610144	25	1	.51	.34	366		144	8	
QG41610168	25	1	.52	.35	427	168	7	15	34	Y
QG41610189	25	1	.49	.33	480	189	7	16	36	X
QG41613120	32	1 1/4	.84	.56	305	120	7	18	39	X
QG41613168	32	1 1/4	.85	.57	427	168	5	18	40	X
QG41615120	38	1 1/2	1.25	.84	305	120	5	19	42	X
QG41615144	38	1 1/2	1.25	.84	366	144	4	18	40	X
QG41615180	38	1 1/2	1.26	.84	457	180	3	17	38	X

Note: Package diameter and type affect product density. Use cartridge count to determine actual explosive charge weight. Note: All weights are approximate.

DYNOSPLIT AP are available in a wide variety of sizes. Custom sizes are subject to surcharge and may require longer than usual lead times. Check with your Dyno Nobel representative should you have any questions.

*Add four pounds for Gross Case Weight

TRANSPORTATION, STORAGE AND HANDLING

- DYNOSPLIT AP must be transported, stored, handled and used in conformity with all applicable federal, state, provincial and local laws and regulations.
- Packaged emulsions have a shelf life of one (1) year when stored at temperatures between -18°C and 38° C (0°F and 100°F). Explosive inventory should be rotated. Avoid using new materials before the old. For recommended good practices in transporting, storing, handling and using this product, see the booklet "Prevention of Accidents in the Use of Explosive Materials" packed inside each case and the Safety Library Publications of the Institute of Makers of Explosives.

Case Dimensions

X	127 x 27 x 16 cm	49.875 x 10.750 x 6.19 in
Y	88 x 28 x 16 cm	34.750 x 10.875 x 6.25 in

ADDITIONAL INFORMATION – Visit dynonobel.com for Brochures and Case Studies related to this product.

Product Disclaimer: Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product. Under no circumstances shall Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.

DYNO®
Dyno Nobel